The PAP-8E Platelet Aggregation Profiler

ROUTINE & SPECIAL AGGREGATION TESTING

RISTOCETIN COFACTOR ACTIVITY ANALYSIS

ANTI-PLATELET DRUG RESPONSES

HEPARIN INDUCED THROMBOCYTOPENIA DETECTION



A COMPLETE TEST SYSTEM

8 Test Channel Aggregometer All-In-One Wireless Computer PAP-8E System Software Electronic Pipette

Microsoft® Office Suite



The Gold Standard in LTA Platelet Function Testing

Bio/Data Corporation's PAP-8E is an advanced platelet aggregometer for clinical and research laboratory applications. Exceptional ease of use and standardized test procedures allow for rapid, routine testing of platelet function. The PAP-8E is designed to support detection and diagnosis of hemostasis disorders, including inherited and acquired platelet dysfunctions. The system measures the rate and extent of activation, aggregation, agglutination and inhibition reactions. Comprehensive results include area under the curve, area under the slope, and user defined analyses.

- Eight Independently Operated Test Channels
- Nine Test Results Reported Per Channel
- Standard Micro-Volume (225uL) Samples
- User-Defined Test Templates & Protocols
- Walk-Away Operation
- Touch Screen Control
- On-Demand Optical Calibration Check
- Two Year Limited Warranty


Trusted Accuracy, Best-In-Class Performance, Simple Operation & Rapid Results






* Printout Enlarged For Detail

Routine Aggregation




Detect & Diagnose Inherited Diseases

von Willebrand Factor



Measure Ristocetin CoFactor Activity

Special Aggregation



Assess Dual Anti-Platelet Therapy & Other **Drug Induced or Acquired Dysfunctions**

SYSTEM COMPONENTS INCLUDED

PAP-8E Platelet Aggregometer

All-In-One Wireless Computer

PAP-8E System Software

Programmable Electronic Pipette with Charging Stand

Microsoft® Office Suite

Color Printer (USA & Canada)

PAP-8E SYSTEM SOFTWARE

- **Routine & Special Aggregation Testing**
- Three or Four Point Standard Curves for Ristocetin CoFactor Assay Activity
- Data Analysis: User Selectable Points & Functions: Primary & Secondary Aggregation, Primary & Secondary Slope, Area Under the Curve, Area Under the Slope, Lag Phase, Shape Change, Disaggregation, Max & Final Aggregation
- **User-Defined Test Templates & Protocols**
- Pre-Loaded Routine & Special Test Parameters
- Walk-Away Operation with User Adjustable Auto Stop Timers & Alarms
- On-Demand Optical Calibration Check
- Trace Filter Selection for Each Test Well
- Database Sorting, Archiving & Backup
- Data Exporting Direct to Excel or Prism®
- Clip Feature Copies Results Into Any Microsoft
- On-Screen Help, Operation & Methods Manuals
- Software Updates Provided Free of Charge During

Warranty Period

ibraltar Road am, PA 19044 USA

Worldwide: +1 215-441-4000 USA: 1-800-257-3282 Fax Worldwide: +1 215-443-8820

customer.service@biodatacorp.com





www.biodatacorp.com

www.bionordika.se 08-306010 infor@bionordika.se

PRODUCT SPECIFICATIONS

PAP-8E Platelet Aggregometer

Eight Independently Operated Test Channels

Eight Stirred Activation Wells

Eight Non-Stirred Incubation Wells

Two Reagent Wells

Light Source: UV LED 400-430nm Automatic Range Adjustment Blank: 250 uL PPP or PFP

Test Sample: 225 uL PRP Reagent / Agonist: 25 uL

Temperature Control: 37°C ± 0.5°C

Temperature Range: 32°C - 45°C; User Adjustable

Stirring: Digital: 0 - 1200 RPM

> Preset for Standard Tests: Operator Controlled for User

Defined Tests

Human and Veterinary: PRP, PPP, PFP, Washed Platelets, Gel Filtered Platelets, Leukocytes,

Red Cells, and AB-AG Solutions

Sensitivity: Agonist Dependent

Results: Nine Test Results Reported

Per Channel

Electrical

Specimens:

Voltage Selector Switch: 120 / 240 VAC, 50 / 60 Hz, 3A Isolated, Grounded Line Required

Computer

All-In-One 21.5" Touch Screen Wireless Computer Windows® 10 Professional Operating System Microsoft® Office Suite

PAP-8E System Software

CATALOG NUMBERS



106075 (USA & Canada)

106077 (Export)

OPTIONAL ACCESSORIES

PDQ®, Platelet Function Centrifuge

Reagent Well Adapters Bar Code Reader

DIMENSIONS

Width: 19.5 inches / 49.53 cm Depth: 21.7 inches / 55.11 cm

21.5 - 25.5 inches / 54.61 - 64.77 cm Height:

(Adjustable Stand)

40.0 pounds / 18.0 kg Weight:

LIMITED WARRANTY

PAP-8E Aggregometer, PAP-8E System Software, Pipette

and Printer: Two Years Parts and Labor

Computer System: Two Years Parts and Labor In-Lab

Service By Dell

PATENTS

USA: 7.453.555 WIPO: W2006127567

CERTIFICATIONS & REGISTRATIONS



EC



REP















40 Parham Drive Eastleigh S050 4NU Hampshire UNITED KINGDOM



Proudly Manufactured in the USA Product Data Sheet #107485 Rev. G

©Bio/Data Corporation 2022



